BASE CONNECTION

TKS GETTING CONNECTED

NOT USED

DSL/TEL   FON 1   LAN 1   LAN 2   LAN 3   LAN 4   Power

1. BASE CONNECTION [Kabel Deutschland]

Your **BASE CONNECTION** must be activated before you can proceed with your Surf'n'Talk set up.

Your **BASE CONNECTION** device will be installed and tested by a Kabel Deutschland technician.

2. Power-up and connect to the BASE

Connect the supplied **AC adapter** to the FRITZ!Box's **POWER** port and then to a power outlet. The green **Power** LED will begin flashing, indicating that the device is powered up and ready for operation.

Connect one of the supplied **LAN cables** to the FRITZ!Box port labeled **LAN 1**, then plug the other end into the **LAN port** on the **BASE CONNECTION** device.

The FRITZ!Box will automatically self initialize. When the **Power** LED stops blinking, go to step 3.

3. Connect your telephone and computer.

Plug a standard analog telephone into the **Fon 1** socket. You can then pick up your phone and dial.

No dial tone? Hang up and then retry in a few minutes. In some cases it may take a few minutes to establish your initial phone connection.

Connect the second **LAN cable** to one of the FRITZ!Box LAN ports: **LAN 2** | **LAN 3** | **LAN 4**. Plug the other end of the cable into the LAN port of your computer. Launch your web browser and start surfing.

Your set-up and activation is now complete!

FRITZ!Box Fon WLAN 7360

LAN CABLE [2x]

AC ADAPTER

FRITZ!Box Wi-Fi

First set up a "wired" connection per these instructions, then proceed with your wireless configuration.

After establishing your initial connection, visit the Support section at the TKS website to download our FRITZ!Box wireless setup guide.

TKS Customer Service & Technical Support
24-hour technical support is only a phone call away.

Service Hotline: 0631 3522 499*

www.tkscable.com   **TKS** A KABEL DEUTSCHLAND COMPANY

* Standard fixed network dialing rates apply, a free call from the TKS fixed network.