

easyTV [on-base] setup guide



TKS TECHNICAL SUPPORT

24/7 Hotline: +49 631 3522 499*

*Standard dialing rates to the German fixed network apply.

© All images and logos copyrighted and are the property of their copyright holders. | 2020.02.17

1. Antenna and Ethernet connection [on-base]



Connect the **ANTENNA** cord to your cable jack's **TV port**, attach the other end to the **CABLE IN** port on the set-top box.



Use the **ETHERNET** cable to connect from the set-top box's **LAN** port to a **LAN** port on the TKS Network Gateway.

NOTE: Please do not connect the set-top box's power cord at this time.

2. HDMI

Connect one end of the **HDMI** cable to the set-top box, and the other to your television set.



3. Power-up

- Connect the supplied AC power adapter to the set-top box and turn on your television set.
- Turn on your easyTV set-top box by pressing the remote's red power button.



4. Initial startup

Television Set - Using your TV's remote control select the set-top box as the input source. Your set-top box will automatically initialize when turned on for the first time, this may take a few minutes. The easyTV welcome screen and main menu will appear indicating that your service is now ready to use.

5. Scan for channels and start watching!

Your set-top box will perform an automatic channel scan with your initial setup. When the scan is finished your easyTV channels will be saved, ready for you to start watching. To select or change channels, press the **SFI** key to display the on-screen program guide. You can also flip up or down through channels by pressing the **+ / - PROG** keys.

TIP: If the main picture or on-screen menu freezes or becomes unresponsive, unplug the set-top box from the power and then reconnect. This reboots the set-top box and will clear most problems.